

# PANEL

Recessed panel



## Features:

Ideal for retrofit of existing T5 or T8 fixtures

2 sizes available with 2.5 mm light guide

Plug and play driver

Emergency option available

Extruded aluminium frame

High performance opal TP[b] diffuser

Compatible with PANEL FRAME

30,000 hours lifetime [L70/B50]

## Construction:

Up to 100 lumens per watt efficacy

Please note daylight [6000K] only available in 600 x 600



# PANEL

Recessed panel

## Order Codes

All dimensions are in millimetres

Order Code	Description	Nominal Size	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCRP6630WW	600 mm x 600 mm Recessed Panel	600x600	3000	30	100	2.73
XCRP6630NW	600 mm x 600 mm Recessed Panel	600x600	3000	30	100	2.73
XCRP6630CW	600 mm x 600 mm Recessed Panel	600x600	3000	30	100	2.73
XCRP6630DL	600 mm x 600 mm Recessed Panel	600x600	3000	30	100	2.73
XCRP12650NW	1200 mm x 600 mm recessed Panel	1200x600	5000	50	100	5.90
XCRP12650CW	1200 mm x 600 mm Recessed Panel	1200x600	5000	50	100	5.90
XCRP12650DL	1200 mm x 600 mm Recessed Panel	1200x600	5000	50	100	5.90

## Dimensions

All dimensions are in millimetres

Order Code	A	B	C
XCRP6630WW	595	595	10
XCRP6630NW	595	595	10
XCRP6630CW	595	595	10
XCRP6630DL	595	595	10
XCRP12650NW	1195	595	10
XCRP12650CW	1195	595	10
XCRP12650DL	1195	595	10

