

PANEL

Recessed LED panel



Features:

Ideal for retro-fit of existing T8 or T5 fixtures

Available in 2 sizes with 2.5mm light guide

Plug and play driver

Emergency option also available

Extruded aluminium frame

Opal polystyrene diffuser

Compatible with PANEL FRAME

SDCM

30,000 hours lifetime (L70/B50)

Construction:

Up to 100 lumens per watt efficacy

Please note daylight (6000K) only available in 600 x 600



PANEL

Recessed LED panel

Order Codes

All dimensions are in millimetres

Order Code	Description	Nominal Size	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCRP6630NW	600mm x 600mm LED Recessed Panel - 4000K	600 x 600	3000	30	100	2.73
XCRP6630CW	600mm x 600mm LED Recessed Panel - 5000K	600 x 600	3000	30	100	2.73
XCRP6630DL	600mm x 600mm LED Recessed Panel - 6000K	600 x 600	3000	30	100	2.73
XCRP12650NW	1200mm x 600mm LED Recessed Panel - 4000K	1200 x 600	5000	50	100	5.90
XCRP12650CW	1200mm x 600mm LED Recessed Panel - 5000K	1200 x 600	5000	50	100	5.90

Dimensions

All dimensions are in millimetres

Order Code	A	B	C
XCRP6630NW	595	595	10
XCRP6630CW	595	595	10
XCRP6630DL	595	595	10
XCRP12650NW	1195	595	10
XCRP12650CW	1195	595	10

