

FLOODLIGHT

LED Floodlight



Features:

Ideal for retro-fit of existing halogen fixtures

Available in 7 different outputs

High quality toughened safety glass

Ideal for lighting buildings, car parks or doorways

Weatherproof IP65 construction

Available with PIR

Choice of black or white body

Supplied with stirrup and 1.0m of flex for column, bracket or surface fix

35,000 hours lifetime (L70/B50)

Construction:

Up to 102 lumens per watt efficacy



FLOODLIGHT

LED Floodlight

Order Codes

All dimensions are in millimetres

Order Code	Description	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCSF10NW	10W LED IP65 Floodlight - 4000K	800	10	80	0.52
XCSF20NW	20W LED IP65 Floodlight - 4000K	1600	20	80	1.01
XCSF30NW	30W LED IP65 Floodlight - 4000K	2700	30	90	1.61
XCSF50NW	50W LED IP65 Floodlight - 4000K	4700	50	94	2.40
XCSF100NW	100W LED IP65 Floodlight - 4000K	9500	100	95	4.74
XCSF150NW	150W LED IP65 Floodlight - 4000K	15300	150	102	5.34
XCSF200NW	200W LED IP65 Floodlight - 4000K	19400	200	97	5.45
XCSF10WW	10W LED IP65 Floodlight - 3000K	700	10	70	0.52
XCSF20WW	20W LED IP65 Floodlight - 3000K	1400	20	70	1.01
XCSF30WW	30W LED IP65 Floodlight - 3000K	2400	30	80	1.61
XCSF50WW	50W LED IP65 Floodlight - 3000K	4100	50	82	2.40
XCSF100WW	100W LED IP65 Floodlight - 3000K	8300	100	83	4.74
XCSF150WW	150W LED IP65 Floodlight - 3000K	13400	150	90	5.34
XCSF200WW	200W LED IP65 Floodlight - 3000K	17000	200	85	5.45

Dimensions

All dimensions are in millimetres

Order Code	A	B	C
XCSF10NW	130	110	40
XCSF20NW	180	150	50
XCSF30NW	225	190	60
XCSF50NW	280	235	70
XCSF100NW	370	310	90
XCSF150NW	425	325	100
XCSF200NW	425	325	100
XCSF10WW	130	110	40
XCSF20WW	180	150	50
XCSF30WW	225	190	60
XCSF50WW	280	235	70
XCSF100WW	370	310	90
XCSF150WW	425	325	100
XCSF200WW	425	325	100

