

FLOODLIGHT PIR

Floodlight



Features:

Ideal for retro-fit of existing halogen fixtures

Available in 4 different outputs

High quality toughened safety glass

Ideal for lighting buildings, car parks or doorways

Weatherproof IP65 construction

Available without PIR

Choice of black or white body

Supplied with stirrup and 1.0m of flex for column, bracket or surface fix

35,000 hours lifetime (L70/B50)

Construction:

Up to 102 lumens per watt efficacy



FLOODLIGHT PIR

Floodlight

Order Codes

All dimensions are in millimetres

Order Code	Description	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCSF10NWP	10W IP65 Floodlight - 4000K	800	10	80	0.52
XCSF20NWP	20W IP65 Floodlight - 4000K	1600	20	80	1.01
XCSF30NWP	30W IP65 Floodlight - 4000K	2700	30	90	1.61
XCSF50NWP	50W IP65 Floodlight - 4000K	4700	50	94	2.40
XCSF10WWP	10W IP65 Floodlight - 3000K	700	10	70	0.52
XCSF20WWP	20W IP65 Floodlight - 3000K	1400	20	70	1.01
XCSF30WWP	30W IP65 Floodlight - 3000K	2400	30	80	1.61
XCSF50WWP	50W IP65 Floodlight - 3000K	4100	50	82	2.40

Dimensions

All dimensions are in millimetres

Order Code	A	B	C
XCSF10NWP	130	110	40
XCSF20NWP	180	150	50
XCSF30NWP	225	190	60
XCSF50NWP	280	235	70
XCSF10WWP	130	110	40
XCSF20WWP	180	150	50
XCSF30WWP	225	190	60
XCSF50WWP	280	235	70

