

DOWNLIGHT

LED Downlight



Features:

Ideal for retro-fit of existing CFL fixtures

Available in 5 sizes

Edge-lit LED array with ultra slim profile

Plug and play remote driver

Emergency option also available

Die-cast aluminium body

Opal polystyrene diffuser

30,000 hours lifetime (L70/B50)

Construction:

Up to 88 lumens per watt efficacy



DOWNLIGHT

LED Downlight

Order Codes

All dimensions are in millimetres

Order Code	Description	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCDL4WW	4W LED Downlight - 3000K	200	4	50	0.20
XCDL4NW	4W LED Downlight - 4000K	250	4	63	0.20
XCDL4DL	4W LED Downlight - 6000K	250	4	63	0.20
XCDL8WW	8W LED Downlight - 3000K	550	8	69	0.20
XCDL8NW	8W LED Downlight - 4000K	600	8	75	0.20
XCDL8DL	8W LED Downlight - 6000K	600	8	75	0.20
XCDL12WW	12W LED Downlight - 3000K	900	12	75	0.31
XCDL12NW	12W LED Downlight - 4000K	1000	12	83	0.31
XCDL12DL	12W LED Downlight - 6000K	1000	12	83	0.31
XCDL15WW	13W LED Downlight - 3000K	1100	13	85	0.40
XCDL15NW	13W LED Downlight - 4000K	1200	13	92	0.40
XCDL15DL	13W LED Downlight - 6000K	1200	13	92	0.40
XCDL17WW	17W LED Downlight - 3000K	1300	17	76	0.55
XCDL17NW	17W LED Downlight - 4000K	1400	17	82	0.55
XCDL17DL	17W LED Downlight - 6000K	1500	17	88	0.55
XCDL22WW	22W LED Downlight - 3000K	1700	22	77	0.81
XCDL22NW	22W LED Downlight - 4000K	1800	22	82	0.81
XCDL22DL	22W LED Downlight - 6000K	1800	22	82	0.81

Dimensions

All dimensions are in millimetres

Order Code	Diameter	C	Cut Out
XCDL4WW	90	25	70
XCDL4NW	90	25	70
XCDL4DL	90	25	70
XCDL8WW	120	25	106
XCDL8NW	120	25	106
XCDL8DL	120	25	106
XCDL12WW	170	25	154
XCDL12NW	170	25	154
XCDL12DL	170	25	154
XCDL15WW	200	25	180
XCDL15NW	200	25	180
XCDL15DL	200	25	180
XCDL17WW	238	25	220
XCDL17NW	238	25	220
XCDL17DL	238	25	220
XCDL22WW	296	25	280
XCDL22NW	296	25	280
XCDL22DL	296	25	280

