

BATTEN

Batten



Features:

- Ideal for retrofit of existing T5 or T8 fixtures
- 4 lengths available
- Integral emergency option available
- Integrated high quality driver and LED module
- Steel body with BESA fixings and rear or end cable-entry
- High quality opal diffuser to reduce glare
- 30,000 hours lifetime [L70/B50]

Construction:

- Up to 133 lumens per watt efficacy



BATTEN

Batten

Order Codes

All dimensions are in millimetres

Order Code	Description	Nominal Size	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCSBT210NW	600 mm Batten - 4000K	600	1150	10	115	0.68
XCSBT417NW	1200 mm Batten - 4000K	1200	2150	17	126	1.25
XCSBT435NW	1200 mm Batten - 4000K	1200	4000	35	114	1.25
XCSBT518NW	1500 mm Batten - 4000K	1500	2400	18	133	1.50
XCSBT528NW	1500 mm Batten - 4000K	1500	3500	28	125	1.50
XCSBT555NW	1500 mm Batten - 4000K	1500	6550	55	119	1.50
XCSBT631NW	1800 mm Batten - 4000K	1800	4050	31	131	1.80
XCSBT660NW	1800 mm Batten - 4000K	1800	7650	60	128	1.80
XCSBT417WW	1200 mm Batten - 3000K	1200	2050	17	121	1.25
XCSBT528WW	1500 mm Batten - 3000K	1500	3350	28	120	1.50
XCSBT528DL	1500 mm Batten - 6000K	1500	3500	28	125	1.50
XCSBT555DL	1500 mm Batten - 6000K	1500	6550	55	119	1.50
XCSBT631DL	1800 mm Batten - 6000K	1800	4050	31	131	1.80
XCSBT660DL	1800 mm Batten - 6000K	1800	7700	60	128	1.80

Dimensions

All dimensions are in millimetres

Order Code	A	B	C
XCSBT210NW	600	55	58
XCSBT417NW	1200	55	58
XCSBT435NW	1200	55	58
XCSBT518NW	1500	55	58
XCSBT528NW	1500	55	58
XCSBT555NW	1500	55	58
XCSBT631NW	1800	55	58
XCSBT660NW	1800	55	58
XCSBT417WW	1200	55	58
XCSBT528WW	1500	55	58
XCSBT528DL	1500	55	58
XCSBT555DL	1500	55	58
XCSBT631DL	1800	55	58
XCSBT660DL	1800	55	58

