

FLOOD

Floodlight



Features:

Ideal for retro-fit of existing halogen fixtures

Available in 7 different outputs

High quality toughened safety glass

Ideal for lighting buildings, car parks or doorways

Weatherproof IP65 construction

Available with PIR

Choice of black or white body

Supplied with stirrup and 1.0m of flex for column, bracket or surface fix

35,000 hours lifetime (L70/B50)

Construction:

Up to 100 lumens per watt efficacy



FLOOD

Floodlight

Order Codes

All dimensions are in millimetres

Order Code	Description	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCFL10NW	10W Floodlight - 4000K	700	10	69	0.85
XCFL20NW	20W LED Floodlight - 4000K	1700	20	85	1.52
XCFL30NW	30W Floodlight - 4000K	2500	30	83	2.25
XCFL50NW	50W Floodlight - 4000K	4300	50	86	3.20
XCFL80NW	80W Floodlight - 4000K	8000	80	100	5.75
XCFL120NW	120W Floodlight - 4000K	11400	120	95	6.52
XCFL160NW	160W Floodlight - 4000K	15900	160	99	7.35
XCFL200NW	200W Floodlight - 4000K	18900	200	95	8.32

Dimensions

All dimensions are in millimetres

Order Code	A	B	C
XCFL10NW	105	115	90
XCFL20NW	150	180	108
XCFL30NW	222	200	108
XCFL50NW	285	235	125
XCFL80NW	395	285	120
XCFL120NW	325	425	165
XCFL160NW	325	425	165
XCFL200NW	325	425	165

