

PANEL BL

Recessed backlit panel



Features:

- Backlit recessed module for retrofit of T5 or T8 installations
- More consistent and uniform appearance than traditional edge-lit panels
- Emergency option available
- Extruded aluminium frame
- High performance opal TP[b] diffuser
- Compatible with PANEL FRAME
- 30,000 hours lifetime [L70/B50]

Construction:

- Up to 100 lumens per watt efficacy
- Supplied in neutral white [4000K], cool white [5000K] or daylight [6000K]



PANEL BL

Recessed backlit panel

Order Codes

All dimensions are in millimetres

Order Code	Description	Nominal Size	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCBLP6630NW	600 mm x 600 mm Recessed backlit Panel	600x600	3000	30	100	1.60
XCBLP6630CW	600 mm x 600 mm Recessed backlit Panel	600x600	3000	30	100	1.60
XCBLP6630DL	600 mm x 600 mm Recessed backlit Panel	600x600	3000	30	100	1.60
XCBLP6630WW	600mm x 600mm Recessed Backlit Panel	600x600	3000	30	100	1.60
XCBLP12650CW	1200mm x 600mm Recessed Backlit Panel	1200x600	5300	50	106	3.90
XCBLP12650DL	1200mm x 600mm Recessed Backlit Panel	1200x600	5300	50	106	3.90
XCBLP12650NW	1200mm x 600mm Recessed Backlit Panel	1200x600	5300	50	106	3.90

Dimensions

All dimensions are in millimetres

Order Code	A	B	C
XCBLP6630NW	595	595	30
XCBLP6630CW	595	595	30
XCBLP6630DL	595	595	30
XCBLP6630WW	595	595	30
XCBLP12650CW	1195	595	30
XCBLP12650DL	1195	595	30
XCBLP12650NW	1195	595	30

