

FRD MINI

Recessed mini fire rated, Downlight



Features:

Compact fire rated downlight with AC on board driver technology

White, satin nickel or polished chrome available

Dimmable as standard

Loop in/out mains connections

Steel body providing a high level of fire protection in accordance with Building Regulations Part B

30, 60 & 90 minute fire rating with solid timber joists

30 minute fire rating with Staircraft I-Joist

Convert to larger sized cut outs with the CONVERSION PLATES

30,000 hours lifetime [L70/B50]

Construction:

Up to 90 lumens per watt efficacy



FRD MINI

Recessed mini fire rated, Downlight

Order Codes

All dimensions are in millimetres

| Order Code | Description | Lumens(lm) | Total Power(W) | Efficacy(lm/W) | Weight(Kg) |
|------------|---------------------------------------|------------|----------------|----------------|------------|
| XCFRA5WWW | 5W Fire rated downlight - White | 400 | 5 | 80 | 0.20 |
| XCFRA5WWSN | 5W Fire rated downlight - Satin nicke | 400 | 5 | 80 | 0.20 |
| XCFRA5WWPC | 5W Fire rated downlight - Polished ch | 400 | 5 | 80 | 0.20 |
| XCFRA5NWW | 5W Fire rated downlight - White | 450 | 5 | 90 | 0.20 |
| XCFRA5NWSN | 5W Fire rated downlight - Satin nicke | 450 | 5 | 90 | 0.20 |
| XCFRA5NWPC | 5W Fire rated downlight - Polished ch | 450 | 5 | 90 | 0.20 |

Dimensions

All dimensions are in millimetres

| Order Code | Diameter | C | Cut Out |
|------------|----------|----|---------|
| XCFRA5WWW | 80 | 80 | 60 |
| XCFRA5WWSN | 80 | 80 | 60 |
| XCFRA5WWPC | 80 | 80 | 60 |
| XCFRA5NWW | 80 | 80 | 60 |
| XCFRA5NWSN | 80 | 80 | 60 |
| XCFRA5NWPC | 80 | 80 | 60 |

