

MINIFLOOD

Miniflood



Features:

Ideal for retro-fit of existing halogen fixtures

Available in 3 body sizes

Supplied with stirrup and 1.0m of flex

High quality toughened safety glass

Die-cast aluminium body

Available in black or white

Low energy and maintenance free solution

30,000 hours lifetime (L70/B50)

Construction:

Up to 75 lumens per watt efficacy



MINIFLOOD

Miniflood

Order Codes

All dimensions are in millimetres

Order Code	Description	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCMF10BDL	10W Miniflood - 6000K - Black	600	10	60	0.32
XCMF10BWW	10W Miniflood - 3000K - Black	500	10	50	0.32
XCMF10WDL	10W Miniflood - 6000K - White	600	10	60	0.32
XCMF10WWW	10W Miniflood - 3000K - White	500	10	50	0.32
XCMF20BDL	20W Miniflood - 6000K - Black	1500	20	75	0.50
XCMF20WWW	20W Miniflood - 3000K - White	1400	20	70	0.50
XCMF20WDL	20W Miniflood - 6000K - White	1500	20	75	0.50
XCMF20BWW	20W Miniflood - 3000K - Black	1400	20	70	0.50
XCMF30BDL	30W Miniflood - 6000K - Black	2000	30	67	0.63
XCMF30WWW	30W Miniflood - 3000K - White	1800	30	60	0.63
XCMF30BWW	30W Miniflood - 3000K - Black	1800	30	60	0.63
XCMF30WDL	30W Miniflood - 6000K - White	2000	30	67	0.63

Dimensions

All dimensions are in millimetres

Order Code	A	B	C
XCMF10BDL	130	90	35
XCMF10BWW	130	90	35
XCMF10WDL	130	90	35
XCMF10WWW	130	90	35
XCMF20BDL	180	126	35
XCMF20WWW	180	126	35
XCMF20WDL	180	126	35
XCMF20BWW	180	126	35
XCMF30BDL	210	147	35
XCMF30WWW	210	147	35
XCMF30BWW	210	147	35
XCMF30WDL	210	147	35

