

FRD MINI TILT CC

FRD MINI TILT CC



Features:

Compact fire rated tilt downlight with AC on board driver technology

CCTK adjustable via simple 3-way selector switch

Dimmable as standard

Loop in/out mains connections with easy-fit connector

White, satin nickel or polished chrome available

Steel body providing a high level of fire protection in accordance with Building Regulations Part B

30, 60 & 90 minute fire rating with solid timber joists

30 minute fire rating with Staircraft I-Joist and METAL WEB Joist (COMPATABILITY MATRIX)

30,000 hours lifetime

Construction:

Convert to larger sized cut outs with the [CONVERSION PLATES](http://www.xciteledlighting.co.uk/products/frd-conversion-plate/)

Up to 100 lumens per watt efficacy



FRD MINI TILT CC

FRD MINI TILT CC

Order Codes

All dimensions are in millimetres

Order Code	Description	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCFRAT5CTW	5W recessed FRD tilt - 3000/4000/6000K - white trim 400-500	400-500	5	100	0.19
XCFRAT5CTSN	5W recessed FRD tilt - 3000/4000/6000K - satin trim 400-500	400-500	5	100	0.19
XCFRAT5CTPC	5W recessed FRD tilt - 3000/4000/6000K - polished chrome trim	400-500	5	100	0.19

Dimensions

All dimensions are in millimetres

Order Code	Diameter	C	Cut Out
XCFRAT5CTW	85	67	65
XCFRAT5CTSN	85	67	65
XCFRAT5CTPC	85	67	65

