

WEATHERPROOF

Weatherproof, polycarbonate luminaire



Features:

Ideal for retrofit of existing T5 or T8 fixtures

3 lengths available

Integral emergency option also available

Polycarbonate body

Stainless steel fixing clips

Supplied with opal diffuser

This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

30,000 hours lifetime (L70/B50)

Construction:

Up to 117 lumens per watt efficacy

Supplied in neutral white (4000K)



WEATHERPROOF

Weatherproof, polycarbonate luminaire

Order Codes

All dimensions are in millimetres

Order Code	Description	Nominal Size	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCWP14NW	1200 mm Weatherproof - 4000K	1200	2300	24	96	2.20
XCWP15NW	1500 mm Weatherproof - 4000K	1500	3400	34	100	2.38
XCWP24NW	1200 mm Weatherproof - 4000K	1200	4700	48	98	2.62
XCWP25NW	1500 mm Weatherproof - 4000K	1500	6800	68	100	3.35
XCWP16NW	1800 mm Weatherproof - 4000K	1800	3800	40	95	2.38
XCWP26NW	1800 mm Weatherproof - 4000K	1800	7500	82	91	3.35
XCWP15HONW	1500 mm Weatherproof - 4000K	1500	6300	54	117	2.38

Dimensions

All dimensions are in millimetres

Order Code	A	B	C
XCWP14NW	1265	100	106
XCWP15NW	1565	100	106
XCWP24NW	1265	155	106
XCWP25NW	1565	155	106
XCWP16NW	1765	100	106
XCWP26NW	1765	155	106
XCWP15HONW	1565	100	106

