xcite LED Lighting

Data Sheet

0.07 0.37

110-240V 55.49

Order Code: XCDK10CT

6W 10-Way Decking Light Kit - CCTK Selector [3000K/4000K]



Features

- Suitable for garden decking and walkways
- Available as 5-way or 10-way kit
- Choice of 6000K or CCTK [3000K/4000K] adjustable
- Adjustment via twist and locking loom system
- Up to 42 lumens per watt efficacy

Construction

- Polished stainless steel [Grade #304] trim with polycarbonate cover
- Supplied with outdoor IP67 LED Driver













Technical Data

General		Electrical
Luminaire Wattage (W)	6	Rated Input Current (A)
Weight (kg)	0.56	Power Factor (pf)
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)
Light Outs	4	Inrush Current Peak (A)
Light Outp Lumens (Im)	250	Surge Protection (kV)
Efficacy (lm/W)	42	
LED		
CCT (K)	3000-4000	
CRI	>80	
Macadam Elipses	5.5	
Driver		
Driver Current (mA)	660mA	
Forward Voltage (V)	12V	



xcite LED Lighting

Data Sheet



Order Code: XCDK10CT

6W 10-Way Decking Light Kit - CCTK Selector [3000K/4000K]

Dimensions

A (mm)	17825
B (mm)	1500
C (mm)	2225
E (mm)	26
Cut Out (mm)	22
Dia. (mm)	30

Line Drawing





