xcite LED Lighting

Data Sheet



Order Code: XCEBNM3ST

1W - Fixed output - Non-maintained Emergency Self-test - 6500K



Features

- Ideal for replacement of linear fluorescent fixtures
- Suitable for escape routes and exits
- 20mm conduit top and rear cable entries BESA for wall fix
- Reduced maintenance and high performance
- EURO 1, 2 and 3 running man legend also available [sold separately]

Construction

- Steel body
- Maintained or non-maintained available
- · Supplied with EURO 4 running man legend
- Integral auto self-test for reduced maintenance















General		Electrical	
Luminaire Wattage (W)	1	Rated Input Current (A)	0.037
Weight (kg)	1.40	Power Factor (pf)	0.19
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	220-240
LED		Conductor Size (mm)	1.5
CCT (K)	6500	Terminal Type	3 pole screw down
CRI	70		
Driver			
Driver Current (mA)	340		
Forward Voltage (V)	2.8		

xcite LED Lighting

Data Sheet



Order Code: XCEBNM3ST

1W - Fixed output - Non-maintained Emergency Self-test - 6500K

Dimensions

A (mm)	392
B (mm)	190
C (mm)	60

Line Drawing



