xcite LED Lighting

Data Sheet



0.029 0.46 220-240

4 pole screw down

Order Code: XCSEBM3

3W - Emergency Slimline Exit Box with Arrow Up Legend - 3hrs Maintained Emergency



Features

- Suitable for open areas and escape routes
- Rear BESA fix and 3 additional rear fixing points
- Reduced maintenance and high performance
- Only 30mm depth for modern, slimline appearance
- Dual LED array for internal illumination and downward distribution
- Test switch fitted for easy testing
- EURO 1,2 & 4 running man legend also available [sold separately]

Construction

- · Plastic body
- · Hinged front lid for easy installation











Technical Data

General			Electrical
Luminaire Wattage (W)	3.2	Rated Input Current (A)	
Weight (kg)	0.65	Power Factor (pf)	
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	
LED		Conductor Size (mm)	
CCT (K)	6500	Terminal Type	
CRI	70		
Driver			
Driver Current (mA)	172		
Forward Voltage (V)	2.7		



xcite LED Lighting

Data Sheet



Order Code: XCSEBM3

3W - Emergency Slimline Exit Box with Arrow Up Legend - 3hrs Maintained Emergency

Dimensions

A (mm)	325
B (mm)	185
C (mm)	30

Line Drawing



