

Order Code: XCSF10NWPW
10W - High Output Slim Floodlight - IP65 - PIR - 4000K - White



Features

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Weatherproof IP65 construction
- Up to 80 lumens per watt efficacy

Construction

- White or black body finish
- Breather gland for reducing condensation

Technical Data

Table with 2 columns: General, Light Output, LED. Rows include Luminaire Wattage (W), Weight (kg), Operating Temperature (ta °C), Lumens (lm), Efficacy (lm/W), CCT (K), CRI, and Macadam Elipses.

Table with 2 columns: Electrical. Rows include Rated Input Current (A), Power Factor (pf), Input Voltage Range (VAC), Inrush Current Peak (A), Surge Protection (kV), Conductor Size (mm), and Terminal Type.

Order Code: XCSF10NWPW

10W - High Output Slim Floodlight - IP65 - PIR - 4000K - White

Dimensions

A (mm)	205
B (mm)	110
C (mm)	52

Line Drawing

