xcite LED Lighting

Data Sheet



Order Code: XCSF200NW

200W - High Output Slim Floodlight - IP65 - 4000K - Black





- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Weatherproof IP65 construction
- Up to 97 lumens per watt efficacy

Construction

- White or black body finish
- Breather gland for reducing condensation














Technical Data

General		E
Luminaire Wattage (W)	200	Rated Input Current (A)
Weight (kg)	5.37	Power Factor (pf)
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)
Light Output	.4	Inrush Current Peak (A)
	19400	Surge Protection (kV)
Efficacy (Im/W)	97	Conductor Size (mm)
		Terminal Type
LED		
CCT (K)	4000	
CRI	65	
Macadam Elipses	4	



xcite LED Lighting

Data Sheet



Order Code: XCSF200NW

200W - High Output Slim Floodlight - IP65 - 4000K - Black

Dimensions

A (mm)	485
B (mm)	325
C (mm)	110

Line Drawing

