

Order Code: XCTLD5CT

5W - Fire Rated Recessed Downlight - Trimless - CCTK Selector [3000K/4000K/6000K] - White



Features

- Compact fire rated downlight with trimless finish
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Dimmable as standard
- Concealed trim for plaster-in finish
- 30, 60 & 90 minute fire rating with solid timber joists
- 30 minute fire rating with Staircraft I-Joist [\[Compatibility Matrix\]](#)
- Up to 100 lumens per watt efficacy

Construction

- Steel body providing a high level of fire protection in accordance with Building Regulations Part B
- Loop in/out mains connections with easy-fit connector
- Integral driver



Technical Data

| General               |         | Electrical                |     |
|-----------------------|---------|---------------------------|-----|
| Luminaire Wattage (W) | 5       | Input Voltage Range (VAC) | 230 |
| Weight (kg)           | 0.37    |                           |     |
| Light Output          |         |                           |     |
| Lumens (lm)           | 400-500 |                           |     |
| Efficacy (lm/W)       | 100     |                           |     |

**Order Code:** XCTL5CT  
5W - Fire Rated Recessed Downlight - Trimless - CCTK Selector [3000K/4000K/6000K] - White

Dimensions

|              |     |
|--------------|-----|
| C (mm)       | 70  |
| Cut Out (mm) | 95  |
| Dia. (mm)    | 145 |

Line Drawing

