

FRD MINI

Recessed fire-rated, Downlight



Features:

- Available in white or satin nickel
- Dimmable as standard
- Integral driver, with loop in/out mains connections
- Steel body with fire rated protection (30, 60 & 90 minute certification)
- Convert to larger sized cut outs with the CONVERSION PLATES
- 25,000 hours lifetime (L70/B50)

Construction:

- Up to 100 lumens per watt efficacy



FRD MINI

Recessed fire-rated, Downlight

Order Codes

All dimensions are in millimetres

Order Code	Description	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCFRD5NWW	5W Fire rated Downlight - 4000K - White	500	5	100	0.27
XCFRD5NWSN	5W Fire rated Downlight - 4000K - Satin nickel	500	5	100	0.27
XCFRD5WWW	5W Fire rated Downlight - 3000K - White	450	5	90	0.27
XCFRD5WWSN	5W Fire rated Downlight - 3000K - Satin nickel	450	5	90	0.27

Dimensions

All dimensions are in millimetres

Order Code	Diameter	C	Cut Out
XCFRD5NWW	80	60	69
XCFRD5NWSN	80	60	69
XCFRD5WWW	80	60	69
XCFRD5WWSN	80	60	69

