

PANEL BL

Recessed backlit panel



Features:

- Backlit recessed module for retro-fit of T5 or T8 installations
- More consistent and uniform appearance than traditional edge-lit panels
- Emergency option also available
- Extruded aluminium frame
- High performance opal TP(b) diffuser
- Compatible with PANEL FRAME
- SDCM
- 30,000 hours lifetime (L70/B50)

Construction:

- Up to 100 lumens per watt efficacy
- Supplied in neutral white (4000K), cool white (5000K) or daylight (6000K)



PANEL BL

Recessed backlit panel

Order Codes

All dimensions are in millimetres

Order Code	Description	Nominal Size	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCBLP6630NW	600mm x 600mm Recessed backlit Panel - 4000K	600 x 600	3000	30	100	1.60
XCBLP6630CW	600mm x 600mm Recessed backlit Panel - 5000K	600 x 600	3000	30	100	1.60
XCBLP6630DL	600mm x 600mm Recessed backlit Panel - 6000K	600 x 600	3000	30	100	1.60

Dimensions

All dimensions are in millimetres

Order Code	A	B	C
XCBLP6630NW	595	595	30
XCBLP6630CW	595	595	30
XCBLP6630DL	595	595	30

